

## FOODSAFE BAKESAFE

Product Code: F- BS (5L, 20L & 200L)

Foodsafe Bake Safe is a graphite, high temperature, chain lubricant for bakery oven chains. Suitable for use on chains running continuously at high temperatures, up to 550°C as a dry film lubricant.

- ✓ Graphite remains in suspension
- ✓ Non-toxic
- ✓ Low odour
- ✓ Non-carbonising
- ✓ High load resistance
- ✓ Rapid penetration of pins and bushes

### DIRECTION OF USE:

Foodsafe Bake Safe is typically applied using automatic lubricators; however, it can also be applied manually by hand, brush, swab, or spray. Once the initial graphite film has been established, Foodsafe Bake Safe may be diluted with up to five parts of water.

### TECHNICAL DATA

<b>Appearance</b>	Black Thixotropic semi fluid
<b>Base / Carrier</b>	Water
<b>Solids</b>	Graphite
<b>Toxicity</b>	Non-Toxic
<b>Stain Characteristics</b>	No stain
<b>Copper</b>	No stain
<b>Mild Steel</b>	
<b>Temperature range</b>	0°C to 550°C

41/47 Horne St, Hoppers Crossing VIC 3029 | [sales@lubex-global.com](mailto:sales@lubex-global.com) | For Tech support call no.: +61 437 300 489 | +61 459 451 000



Last Revised date: 15/04/2025

Data Sheets are updated frequently. Please ensure that you have a current copy. This Datasheet summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since the manufacturer/supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this Datasheet in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, which are available on request.