

BANGCHAK GE NGV

Lubricant for NGV/CNG/LPG vehicles



BANGCHAK GE NGV is multigrade synthetic technology oil SAE15W-40. It's developed for gasoline engines which are modified to be NGV/CNG/LPG. It's blended with high quality base oil, synthetic base oil and premium additive. It's designed for the engines which are modified for NGV/CNG/LPG, gasoline and gasohol fuel.

- o Durable for work in temperature of NGV, CNG and LPG engine that ensures it truly long-drain oil
- o Premium additive for making excellent engine cleanliness
- o High performance for lubricating the engine all situations
- o It has been tested in the vehicles which were modified for NGV/CNG/LPG

MEET REQUIREMENT

- o ACEA A3/B4-23
- o MB 229.1

APPLICATION

- o Capable for gasoline engine which modified for NGV/CNG/LPG included general gasoline engines.

TYPICAL INSPECTION

PROPERTIES	METHOD	BANGCHAK GE NGV SAE 15W-40
Appearance	Visual	Bright & Clear
Color	ASTM D1500	Report
Density @ 15 °C, g/cm ³	ASTM D1298	Report
Flash Point (COC), °C	ASTM D92	215 Min
Foam Test (Seq II), mL/mL	ASTM D892	50/0 Max
Pour Point, °C	ASTM D97	-21 Max
Kinematic Viscosity @ 100 °C, cSt.	ASTM D445	14.5-15.5
Viscosity Index	ASTM D2270	135 Min
Cold Cranking Simulator @ -20 °C, cP	ASTM D5293	6600 Max
TBN, mg KOH/g	ASTM D2896	9.2 Min

FEATURES & BENEFITS



Engine
Protection



Strong Oil Film



Heat Resistance



Prolong
Engine Life

Packaging : 1 Litre, 4 Litres, 18 Litres and 200 Litres

Additional Information Available at www.bangchaklubricants.com

Bangchak Corporation Public Company Limited. 2098 M Tower Building, Sukhumvit Road, Phraknong, Bangkok, Thailand